

user instructions and warranty

camel

freedom

through lightweight solutions

The CAMEL by Mangar International, is an inflatable lifting device which is designed to sit up and lift a fallen person from the floor. When inflated, the CAMEL lifts the patient into a raised seated position ready to stand with or without assistance.

This equipment may be used with or without a helper as required.

The CAMEL is powered by a Mangar International Airflo Compressor and controlled using a CAMEL Hand Control. Please refer to the separate Airflo compressor instructions before operating.

Patents Pending



PLEASE BE SURE THAT YOU HAVE READ AND UNDERSTOOD THESE INSTRUCTIONS AND THOSE PROVIDED WITH THE AIRFLO, BEFORE OPERATING THIS EQUIPMENT.

CONTENTS

- Pg 3 Standard Package Contents
- Pg 3 Connecting the Hand Control and Airflo
- Pg 3 Extra Air Flow
- Pa 4 Airflo 'Auto' Control Button
- Pg 4 Positioning the patient on the CAMEL
- Pg 4 Using the CAMEL
- Pg 6 After Use
- Pg 6 Maintenance
- Pg 6 Routine Cleaning & Disinfecting
- Pg 6 Specifications
- Pg 7 Symbols used on packaging
- Pg 7 Warranty




WARNINGS

- This equipment MUST only be used by persons familiar in its use.
- The medical state of a person needing to be raised MUST be assessed before commencing a lift.
- Ensure that the surface on which the CAMEL is to be placed is free from sharp objects.
- If the slide sheet has been used to transfer the patient onto the CAMEL it must be removed from under the patient before commencing a lift.
- Sections 2, 3 and 4 MUST always be fully inflated in sequence from the bottom up, in order to maintain stability. NOTE: The backrest may be partially inflated before any other section is raised. Once the lowest section is fully inflated, the backrest can be raised further as required.



ME0074 issue 2 Camel



Standard Package Contents - fig. (1)

- 1 x CAMEL (A) including carrying bag (not shown)
- 1 x CAMEL Hand Control (B)
- 2 x Airflo Compressors (C) with user instructions
- 1 x Slide Sheet (not shown)
- 1 x Transfer Belt (not shown)

Connecting the Hand Control and Airflo - fig. (2)

- Remove the CAMEL from the carrying bag, unfasten the straps and unroll.
- Connect the four hoses (A) from the Hand Control to the corresponding numbered and colored connectors on the CAMEL.
- Connect the hose (B) from the Hand Control to the Airflo compressor.
- Position the Airflo compressor so that it will not be in the way while positioning the patient. Ensure that the hoses are not kinked.

Extra Air Flow - fig. (3)

• Select the 'High' Air Flow using the switch on the underside of the Airflo compressor (**D**).



WARNING: DO NOT operate the Normal/High air flow switch while the compressor is running.

(3)

Airflo 'Auto' Control Button - fig. (4)

The 'Auto' function must be selected in order to operate the CAMEL Hand Control. When selected, the Airflo will work automatically when the CAMEL Hand Control buttons are pressed.

- To switch the 'Auto' function on, press and hold the button (A) for a few seconds until the LED (B) lights up.
- To switch the 'Auto' function off, Press any of the Airflo buttons.

WARNING: Pressing any of the Airflo buttons will cancel the 'Auto' function and the hand control will not work

Positioning the patient on the CAMEL - fig. (5)


- Position the CAMEL at the side of the patient so that the patient's head is level with the CAMEL badge (A).
- Transfer the patient onto the CAMEL. The head should lie on the CAMEL badge (A) and the body should lie centrally.

Using the CAMEL

The following instructions apply equally when the CAMEL is being operated by a person raising themselves without assistance, or by an assistant raising a patient.

WARNING: If the slide sheet has been used to transfer the patient onto the CAMEL it must be removed from under the patient before commencing a lift.

- Press the number 1 button on the CAMEL Hand Control to partially inflate the backrest section until the patient is in a comfortable position - fig. 6
- Press the number 2 button to inflate the bottom section fig. (7) until it becomes rigid.





ME0074 issue 2 Camel



• Continue to press buttons 3 and 4 **in sequence** until the sections become rigid, in exactly the same manner - fig. (8)



 Press button 1 to fully raise the backrest and arrive at a sitting position - fig. 9



• Whether assisted or used alone, the patient should now be in a position to stand or transfer - fig. 10

WARNING: In order to maintain stability, sections must always be fully inflated from the bottom up, in sequence.

Note: only the backrest (section 1) may be partially inflated before the lower sections.

After Use

- To deflate, disconnect each of the air hoses from the CAMEL by pushing the release collar on the connector away from the hose and then pulling the hose clear of the connector. NOTE: The initial 'rush' of air as the hoses are disconnected from the CAMEL, can be reduced by first disconnecting the air hose from the Airflo and then pressing each of the buttons on the hand control.
- Roll up the CAMEL with the Hand Control in the hollow (A) fig. (11) secure the straps and place in the carrying bag fig. (12)

Maintenance

Other than routine cleaning, the CAMEL is maintenance free. The backrest section or the main lifting section can be replaced separately if required.

We recommend that a thorough examination of the CAMEL is carried out regularly; the frequency of examination may need to be increased depending on usage and operating environment.

Routine Cleaning

Inflate the CAMEL, sponge clean with a detergent solution and dry thoroughly before storing in a dry place. Do not dry using hot air.

Disinfecting


Inflate the CAMEL, pre-clean with a detergent solution and then sponge with a disinfecting solution or alcohol impregnated wipe. Allow to air dry before storage. Do not dry using hot air.

Specifications

Maximum user weight: 700lbs Seat height (approx): 22" Overall length (approx): 44" Overall width (approx): 27½"


Deflated & rolled (in bag):

Length: 30"
Diameter: 8"
Weight (Inc. Hand Control): 14lbs
Maximum air pressure: 5psi
Max / Min temperature: +120/-60°F





camel



Warranty

Mangar International guarantees this product for a period of two years.



The guarantee is given against defects in material and workmanship and comprises piece, parts and labor. The guarantee is not valid in the case of fair wear and tear, wilful damage, common neglect, misuse or unauthorized alteration or repair by unqualified persons.

The following statements do not affect the consumer's statutory rights. This product is sold on the understanding that in the event of any defect of manufacture or material appearing within two years of the date of receipt of this product, the defect will be rectified free of charge providing that:

- (a) Reasonable evidence is provided (e.g. purchase invoice, delivery note) that the product was not purchased more than two years prior to the date of the claim.
- (b) The defect is not attributable to accidental damage (either in transit or otherwise), misuse or unauthorized repair.

CAMEL serial number:	
Airflo serial number:	
Date of purchase:	
Invoice/Delivery note number:	

Mangar International reserves the right to alter product specifications and/or any of the information contained within this document without notice.

freedom through lightweight solutions



Mangar Inc.

1111 Jupiter Rd. Suite 209-C Plano TX 75074

800-901-5269 toll free 972-424-4100 local 972-424-0060 fax

www.mangar-inc.com

Mangar International
Presteigne
Powys
LD8 2UF
Wales, UK

tel: +44(0)1544 267674 fax: +44(0)1544 260287