



The Jazzy Air® is a new era in power mobility. Whether at home, or out on the town, the unique appeal of Jazzy Air will elevate your independence and social confidence in style.

- Elevate up to 10 inches in 16 seconds
- Enjoy face-to-face social engagement
- Safely drive elevated at walking speed (3.5 mph)



Specifications

Weight Capacity	300 lbs.
Maximum Speed ¹	Up to 4.0 mph (non-elevated position) Up to 3.5 mph (elevated position)
Ground Clearance ²	2.42" at footplate 1.00" at motor bracket
High-Back Seat to Floor Range	23" - 32.9"
Turning Radius ²	22.5"
Overall Size ^{2,6}	Length: 42.23" with foot rigging; 38.6" w/out foot rigging Width: 23.4" at the wheels 25.5" with armrests
Drive Controller	PG VR2
Drive Wheels	10" flat free
Caster Wheels	6" solid caster
Suspension	Active-Trac® with Mid-Wheel 6® Technology
Range ^{1, 4}	Up to 15.29 miles w/ U1 batteries Up to 18.4 miles w/ 40 Ah batteries
Component Weights ⁵	Base: 225 lbs. w/ U1 batteries 245 lbs. w/ 40 Ah batteries Batteries: U1-24.5 lbs. 40 Ah-32.2 lbs.
Drivetrain	Two motor, Mid-Wheel 6® drive
Brakes	"Intelligent Braking" (electronic regenerative, disc park brakes)
Batteries ³	(2) 12 V, U1 (2) 40 Ah
Battery Charger	3.5 amp, off-board
Max. Allowable Incline	6°
Max. Angle Capacity	6°
Maximum Obstacle Climbing Ability	Lowered Position: 2.2" Elevated Position: 1.8"
Warranty	5 year limited (frame) 13 month limited (electronics) 13 month (drive motors)

- Varies with base model, user weight, terrain type, battery amp hour rating (Ah), battery charge, battery condition, motors, controller type, tire type, and tire condition. This specification is subject to a variance of +10%, -5%.
- Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 3) AGM or Gel-Cell type required. See VI. "Batteries and Charging."
- 4) Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5) Battery weight may vary based on manufacturer.
- 6) Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

NOTE: This product conforms to all applicable ANSI/RESNA, ISO 7176 Series, and EN12184 standards. All specifications subject to change without notice.



Find a compatible lift for your vehicle online: PRIDEMOBILITY.COM/LIFT-FINDER

Features

- Achieve 10" of power adjustable seat height in 16 seconds
- Elevate or lower seat height while on the move with the "Air" button or PG VR2 joystick drive controller
- Seat and integrated footplate design provides maximum comfort in both elevated and non-elevated positions
- Angle adjustable footplate with three height adjustments
- Choice of 16" x 16"-18" depth adjustable, high-back, reclining sport seat
- Choice of 18" x 18"-20" or 20" x 20"-22" depth adjustable, fold-flat, high-back reclining sport seat
- Choice of 16" x 16"-18", 18" x 18"-20" and 20" x 20"-22" fold-flat solid seat pan
- Angle, height and depth adjustable armrest
- · Bright LED marker lights
- 60" lap belt

Accessories

- · Rear basket
- · Weather cover
- Cup holder
- Flag kit
- · Cell phone holder
- · Cane holder
- · Walker holder
- · Oxygen holder
- · Saddle bag
- Replacement shroud (ten available colors)
- Alternative size lap belt: 50", 70", 80", 90"
- · XLR USB Charger

Options

- · 40 amp AGM batteries
- · Swing-away joystick
- Synergy[®] Cushions
 - Solution®
 - Solution® 1
 - Spectrum® Gel
 - Spectrum® Foam

Colors



Authorized Pride® Provider

(US) 800-800-8586 • (CAN) 888-570-1113 • pridemobility.com